

- Process to **clean membrane** water filter unit back-flushes permeate side - involves partially or fully emptying separated particles treated with an oxidising agent, back-flushing and tangential rinse, etc..

L20 ANSWER 86 OF 121 WPINDEX COPYRIGHT 2002 DERWENT INFORMATION LTD

AN 1999-096840 [09] WPINDEX

DNC C1999-028766

DC D15 J01

IN SAIER, H

PA (MICR-N) MICRODYN MODULBAU GMBH & CO KG

CYC 1

PI DE 19730441 A1 19990121 (199909)\* 6p

ADT DE 19730441 A1 DE 1997-19730441 19970716

PRAI DE 1997-19730441 19970716

AN 1999-096840 [09] WPINDEX

AB DE 19730441 A UPAB: 19990302

In a process to clean a dead-end or micro-filtration membrane water filter unit, the filter is freed of filtered residues by back-flushing from the permeate side and/or the direction of a tangential rinse on the filter fluid side. The improvement is that: (a) prior to the back-flush action, the filter is partially or fully emptied, the separated particles are treated with an oxidising agent; (b) the first action (a) is followed by back-flushing and tangential rinse; (c) the oxidation process is effected at enhanced temperature between 70 and 160 degrees Celsius; (d) the oxidation agent is oxygen-enriched **air mixed** with steam; (e) the process is undertaken at a pressure of between 1 and 6 bar; (f) the cleaning and filtration processes are carried out alternately.

USE - Process to clean a dead-end or micro-filtration membrane water filter unit.

ADVANTAGE - The process is simple, cheap, effective, requires little energy, and reduces the frequency with which chemical treatment is necessary.

Dwg.0/2

**BEST AVAILABLE COPY**